



PEGASUSTM

FS

4-needles, feed-off-the-arm,
interlock stitch machine
for flatseaming



Handles difficult-to-sew fabrics easily!

Produces uniform stitches on difficult-to-sew fabrics, increasing quality

These machines flatseam difficult-to-sew fabrics, as typified by two-way stretch fabrics, and perform various operations, with uniform stitches, achieving unmatched, high quality finished products.

Easy-to-use machines allow stress-free sewing, increasing production.

The operator can feed cross-seam sections effortlessly, thus ensuring much higher operation efficiency.

Sews a wide range of garments, such as underwear and wetsuits

This new version includes a full line of subclasses that meet the diversified needs of the market.



FS700 Series Subclasses

Type of machine	Model	Remarks
Joining shoulder of T-shirts and underwear, Attaching fly of brief	FS701-G0	*With single edge trimming *For light weight fabrics
Joining shoulder of T-shirts and underwear Attaching fly and Joining crotch of brief	FS701-G1	*With single edge trimming *For light weight fabrics
Joining shoulder of T-shirts and underwear, Attaching fly of brief	FS703-G3	*With double edge trimming *For light to medium weight fabrics
Joining shoulder of T-shirts and underwear Attaching fly and Joining crotch of brief	FS703-G4	*With double edge trimming *For medium weight fabrics
Joining crotch of brief, Attaching gusset of panty	FS703A-G4	*With double edge trimming *For medium to heavy weight fabrics
Joining crotch of wet suits and brief (after binding tape with elastic)	FS703B-G4	*With double edge trimming *For heavy to extra heavy weight fabrics
Joining side of sports wear	FS713-G0	*With double edge trimming *For light to medium weight fabrics
Joining side and crotch of light wet suits	FS713A-G0	*With double edge trimming *For medium to heavy weight fabrics

Seam





FS

4-needles, feed-off-the-arm,
interlock stitch machine
for flatseaming



Specifications

No. of needles:	4
No. of threads :	6
Seam width:	5.2mm, 6.0mm
Stitch length:	Up to 2.5mm
Differential feed ratio:	1:0.7 - 1:1.5
Presser foot lift:	Up to 5.5mm
Machine speed:	4,200rpm (Depends on sewing conditions)



PEGASUS®

PEGASUS SEWING MACHINE MFG.CO.,LTD.
5-7-2, Sagisu, Fukushima-ku, Osaka 553-0002, Japan
Phone:81-6-6458-4739 Telefax:81-6-6454-8785
<http://www.pegasus.co.jp>

The specification and/or appearances of the equipment described in this catalog is subject to change because of modification without previous notice.

